

DCS Side Burners Specifications

| | Single Burner | Double Burner | Single BI Burner | Double BI Burner |
|--|------------------|------------------|------------------|------------------|
| Model Number: | BGB131 | BGB132 | BGB131-BI | BGB132-BI |
| Built-In Installation | - | - | Y | Y |
| Side Burner | 1 @ 17,000 BTU | 2 @ 17,000 BTU | 1 @ 17,000 BTU | 2 @ 17,000 BTU |
| Stainless Steel Cover | Y | Y | Y | Y |
| Dimensions | | | | |
| Overall Width | 13" | 13" | 14 9/16" | 14 9/16" |
| Overall Depth | 15 3/4" | 26 3/4" | 16 1/16" | 26 5/8" |
| Overall Height | 10 5/8" | 10 5/8" | 10 5/8" | 10 5/8" |
| Cutout Width | NA | NA | 12 1/8" | 12 1/8" |
| Cutout Depth | NA | NA | 12" | 22 3/4" |
| Cutout Height | NA | NA | 10 1/8" min. | 10 1/8" min. |
| Gas Option | LP or NAT | LP or NAT | LP or NAT | LP or NAT |
| Electrical Requirements *for ignition | 1.5 Volt Battery | 1.5 Volt Battery | 1.5 Volt Battery | 1.5 Volt Battery |
| Approx. Shipping Weight | 32 lbs | 46 lbs | 32 lbs | 46 lbs |

Gas Requirements

Natural: 1/2" NPT male with a 3/8" flare adapter. Operational Pressure 4" W.C. Supply Pressure 6" to 9" W.C.

Propane: 1/2" NPT male with a 3/8" flare adapter (uses the LP regulator from the adjoining grill). Operational Pressure 11" W.C. Supply Pressure 12" to 14" W.C.

Specifications shown on this page are for reference only. For complete information on installation requirements, please refer to www.dcsappliances.com in the USA and www.dcsappliances.ca in Canada.